



M A S O N I T E




8 KITCHENS




POWDER BAR

BUILT-IN *furniture*



COMBINATION BED




BUILT-IN WARDROBE

Contents include:

**8 SUPER KITCHENS,
BUILT-IN WARDROBE,
ROOM DIVIDER, ETC.**

Complete with working drawings!




ROOM DIVIDER




BUILT-IN SEATS

T H R E E S H I L L I N G S



**KITCHEN 'U' PLAN
No. 1 (Pages 5-8)**




**KITCHEN 'U' PLAN
No. 2 (Pages 9-11)**

index

Kitchens 1 and 2 — Illustrations	2
Kitchens 3 and 4 — Illustrations	3
Kitchens 5, 6, 7 — Illustrations	4
Kitchen 'U' Plan No. 1	5-8
Kitchen 'U' Plan No. 2	9-11
Pre-expansion of Masonite	12
Doors and Drawers — Handy Hints	12
Kitchen 'U' Plan No. 3	13-16
Kitchen '≡' Plan No. 4	17-18
Kitchen 'L' Plan No. 5	19-20
Kitchen 'U' Plan No. 6	21-23
Kitchen '≡' Plan No. 7	24-25
Kitchen 'U' Plan No. 8	26-28
Built-in Wardrobe	29-31
Powder Bar	32
Room Divider	33
Masonite Presdwoods	34
Combination Bed	35
Setting out a Cabinet Frame	36
Kitchens 8 and 9 — Illustrations	37
Powder Bar — Illustration	37
Room Divider — Illustration	38
Combination Bed — Illustration	38
Masonite Shorts	39
Masonite Mouldings	39
Masonite Tools	39

Erratum: Read "Kitchen 'U' Plan No. 1"
instead of "Kitchen 'U' Plan No. 2," page 8.



**KITCHEN 'U' PLAN
No. 3 (Pages 13-16)**

Foreword . . .

In introducing "Built-in Furniture," Masonite Corporation (Aust.) Limited has endeavoured to satisfy the continual requests for more designs of kitchen cabinets and the usual built-in furniture such as wardrobes, powder bars, etc. It should be fully understood that the designs shown are intended only as a guide: for this reason room sizes have been omitted.


Whilst we will not provide an adaption of any particular plan to suit your specific room dimensions, a suitable plan can be adapted to specific dimensions by following the method of setting out cabinet frames (page 36). Similarly the Built-in Wardrobe (page 29) can be extended or reduced by increasing or decreasing the dimensions of the side cupboards or alternatively additional room size may be taken up by facing the remaining space.

As in all publications we have endeavoured, through several inspections, to eliminate any possible errors; but we will not accept responsibility for any error or misprint. The reader is expected to have a basic knowledge of carpentry and there are many wood-working publications available from booksellers to further that knowledge.

Note: Furniture Designs, Volumes I and II, will not be reprinted.



**KITCHEN '≡' PLAN
No. 4 (Pages 17-18)**



KITCHEN 'L' PLAN No. 5


(Pages 19-20)

Designed for the room with corner windows and a sunny aspect, this kitchen will prove a boon to the busy housewife. Efficiently designed and labour saving, Kitchen number 5 may be the answer to your space problem. Handy Masonite Peg-board utensil racks add a modern touch, and attractive Masonite Leatherboard in grain and tone finish for the dining alcove completes the picture.

KITCHEN 'U' PLAN No. 6

(Pages 21-23)


The popular "U" shape has been changed to permit the addition of a snack bar—a handy asset for quick serving of meals. The housewife will appreciate the convenience of the pivotted corner cupboard which can be adapted to all "U" and "L" shape kitchens.




KITCHEN '=' PLAN No. 7

(Pages 24-25)

For the handy man who desires a minimum of work, this kitchen has been designed with sliding doors. Optional cabinets on one wall may be eliminated if sufficient kitchen width does not permit free movement.







PLAN

GENERAL ARRANGEMENT OF FIXTURES

NOTE: $\frac{3}{16}$ " MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.




ELEVATION 3.




ELEVATION 1.

CONTAINER MUST CLEAR SINK TRAP




SECTION 'A-A'

LAMINATE TWO THICKNESSES OF $\frac{3}{16}$ " MASONITE STANDARD PRESWOOD TO FORM SHELVES WHERE SHOWN AS THUS




SECTION 'B-B'

SHELVES SPACED TO SUIT
THIS DOOR SHEETED BOTH SIDES $\frac{3}{16}$ " MASONITE STANDARD PRESWOOD



SECTION 'C-C'



ELEVATION 2.

MATERIAL LIST (Approximate only)			
TIMBER (Finished Size)	LINEAL FEET	TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	400	1 3/4 ins. x 3/4 in.	110
2 3/4 ins. x 3/4 in.	8	2 3/4 ins. x 3/4 in.	50
4 ins. x 3/4 in.	45	4 ins. x 1 1/2 ins.	20
5 ins. x 3/4 in.	15	7 7/8 ins. x 3/4 in.	6
5 ins. x 1/2 in.	36	1/4" Masonite	
3/16" Masonite		Tempered Presdwood	16 sq. ft.
Tempered Presdwood	25 sq. ft.	3/16" Masonite	
Standard Presdwood	250 sq. ft.	Standard Presdwood or Leatherboard	145 sq. ft.
Masonite Pegboard	14 sq. ft.		
1 3/4 ins. x 3/4 in.	240		
4 ins. x 3/4 in.	6		
3/16" Masonite			
Standard Presdwood	180 sq. ft.		


NOTE: Material list is intended only as a guide and is not complete for all requirements.




MASONITE PRESWOOD — LIFETIME SATISFACTION WITH
MAXIMUM ECONOMY — MADE IN AUSTRALIA FOR
AUSTRALIA.

KITCHEN
'U' PLAN
No. 1


PAGE
5



NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.





FRAME... OVERHEAD & STORAGE CABINET




FILLER STRIPS

SEE DETAIL AT 'U'




FRAME... BASE CABINET

ELEVATION '2'



TOWEL RACK DETAIL 'X'

ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.



DETAIL OF SIDE OF TOWEL RACK & RUNNER






TABLE PLAN




SECTION 'D-D'

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.


SHEET THIS FACE WITH 3/16" MASONITE STANDARD PRESWOOD BEFORE FIXING CENTRE SHELF

SHEET BOTH SIDES CENTRE SHELF 3/16" MASONITE STANDARD PRESWOOD


SHEET TOP OF CENTRE SHELF BEFORE FIXING




SECTION 'E-E'



DETAIL 'V'
WASTE DISPOSAL UNIT




BRACKET DETAIL
WASTE DISPOSAL UNIT




FRAME... BASE CABINET
ELEVATION '1'

ALL TIMBER 3 1/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.


FRAMES... OVERHEAD CABINETS
ELEVATION '2'




FRAME... BASE CABINET
ELEVATION '3'



KICK BASE CORNER DETAIL
ELEVATION '3'




FRAME... BASE CABINET
ELEVATION '2'



PLAN

GENERAL ARRANGEMENT OF FIXTURES


MINIMUM
CLEARANCE
WINDOW SILL
TO SINK TOP
6" FOR EASY
ACCESS TO TAPS




MATERIAL LIST (Approximate only)

TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	100
2 3/4 ins. x 3/4 in.	30
4 ins. x 3/4 in.	14
3/16" Masonite	
Tempered Presdwood	62 sq. ft.
Masonite Pegboard	7 sq. ft.
1 3/4 ins. x 3/4 in.	375
2 3/4 ins. x 3/4 in.	7
4 ins. x 3/4 in.	60
5 ins. x 1/2 in.	30
5 ins. x 3/4 in.	9
6 1/2 ins. x 1/2 in.	18
6 1/2 ins. x 3/4 in.	5
3/16" Masonite	
Tempered Presdwood	18 sq. ft.
3/16" Masonite	
Standard Presdwood	240 sq. ft.
Masonite Pegboard	40 sq. ft.
1 3/4 ins. x 3/4 in.	140
3/16" Masonite	
Standard Presdwood	85 sq. ft.


NOTE: Material list is intended only as a guide and is not complete for all requirements.




ELEVATION 1.




ELEVATION 3.




ELEVATION 4.




ELEVATION 2.



SECTION 'A-A'



SECTION 'B-B'



SECTION 'E-E'

ALL DOORS ON BASE CABINETS SHEETED ON THE INSIDE WITH MASONITE PEGBOARD




MASONITE PRIMECOTE — SAVES TIME, ELIMINATES SEALER AND PRIME COATS — WILL TAKE ANY PAINT FINISH.



KITCHEN
'U' PLAN
No. 2

PAGE
9





FRAME ...
OVERHEAD CABINET
ELEVATION 'I'





NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES, EXCEPT WHERE OTHERWISE STATED.




FRAME ... BASE CABINET

ELEVATION '2'

ASK YOUR MASONITE DISTRIBUTOR FOR A FREE SET OF MASONITE LITERATURE ... INCLUDES BENDING, PAINTING, STAINING, ADHERING, ETC., AND OTHER INFORMATIVE DATA.

CORNER BLOCK CUT FROM 4" x 3" TIMBER TO 3 3/4" x 2 3/4" x 8 1/2" L (6" RADIUS)



ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.



MASONITE PRESWOOD, THE BEST WOOD — THE BUILDING BOARD OF TO-DAY AND TOMORROW.

KITCHEN
'U' PLAN
No. 2

PAGE
11

PRE-EXPANSION OF MASONITE PRESWOOD



The manufacture of Masonite Presdwood involves great heat and pressure, so that when the board is first produced it is in its driest possible state. If the board is fixed while in this condition, it is only to be expected that, when atmospheric moisture increases, the board may slightly expand, and tend to wave or buckle.

To counteract this, it is essential to thoroughly wet the boards on the screen side, using 3 to 4 pints of water per full 12 ft. x 4 ft. sheet, and brush the water in with a stiff broom. They should then be stacked flat, screen side to screen side, and allowed to lie in this condition for at least 48 hours, or longer, before application. In this way the boards can assume their natural size and the moisture content is stabilized. When the boards are fixed or nailed no further expansion will occur. The one wetting is sufficient.

DOORS AND DRAWERS - HANDY HINTS

Framing — The timber framework should be of adequate dimensions to suit the particular construction; generally, in small cabinet frames, 2 in. x 1 in. nominal size timber is sufficient. For $\frac{1}{8}$ in. Presdwood we recommend that the space between intermediate battens or rails should be no more than 9 in. and for $\frac{3}{16}$ in. Presdwood the space between the rails to be no more than 12 in; the space can be increased for $\frac{1}{4}$ in. and $\frac{5}{16}$ in. Presdwoods.


Our general experience has shown that it is far more desirable to have small dimensioned intermediate rails at closer centres rather than large dimensioned rails at wider centres. Timber frames should be constructed by using either dowelled, mortised and tenoned joints or corrugated box fasteners. The timber should be machined to an even thickness, all joints planed true and frames squared and vented before applying Masonite Presdwood panels. For large door construction, we recommend the use of wood edge strips to prevent damage and give a much cleaner appearance to door edges. For doors or frames which are expected to remain "true," Masonite Presdwood panels should be fastened to both sides of frames.

Fastening — We recommend the use of adhesives, such as animal glues, casein cement or urea formaldehyde. The longer period allowed with casein cement when laying up frames, etc., makes this adhesive more desirable than animal glues in production work. The adhesive should be spread evenly over all the frame to be glued. Presdwood panels should be then positioned on frames and may be held in place with two small brads until the pressure is applied by press or cramps. Make certain that all air and surplus adhesive is forced out of the joint, allowing at least 3 to 4 hours in press and 24 hours for adhesive to set before working on frames. Wherever possible it is desirable to avoid nailing (other than where required to hold panel in position in press) on surfaces of panels that are to be painted or polished.

FREE LITERATURE






Write to the Sales Offices of Masonite Corporation (Aust.) Ltd. at Melbourne, Sydney, Adelaide or Brisbane for technical leaflets on how to use and finish Masonite Presdwood!

DOOR SECTIONS




SMALL DOOR FRAMES


When using corrugated fasteners for jointing, hold the door frame firmly with sash cramps, check the diagonals and drive home the fasteners with cramps in position.




CORNER DRAWER DETAIL




KICK RAIL DETAIL






PLAN
GENERAL ARRANGEMENT OF FIXTURES




ELEVATION 1.




ELEVATION 2.


NOTE: 3/4" MASONITE STANDARD PRESWOOD
USED ON ALL FACES, EXCEPT WHERE OTHERWISE STATED.




ELEVATION 3.




ELEVATION 4.




ELEVATION 5.



SECTION 'A-A'



SECTION 'E-E'



SECTION 'F-F'



**MASONITE LEATHERBOARD — EMBOSSED SURFACE
PATTERN SIMULATES A SPANISH GRAIN LEATHER . . .
IDEAL FOR BUILT-IN SEATS.**

**KITCHEN
'U' PLAN
No. 3**

PAGE
13

MATERIAL LIST (Approximate only)


TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 ins. TOP CABINETS	200
3/16" Masonite Standard Presdwood	125 sq. ft.
1 3/4 ins. x 3/4 ins.	125
2 1/4 ins. x 3/4 ins.	16
2 3/4 ins. x 3/4 ins. SEATS AND	8
4 ins. x 3/4 ins. TABLE	22
3/16" Masonite Standard Presdwood	96 sq. ft.
3/16" Masonite Tempered Presdwood	12 sq. ft.

NOTE: Material list is intended only as a guide and is not complete for all requirements.


FRAME... OVERHEAD CABINET

ELEVATION '2' & '4'

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES, EXCEPT WHERE OTHERWISE STATED




TYPICAL DRAWER CONSTRUCTION




SECTION 'B-B'


SECTION 'C-C'



EXACT SIZE MAY BE OBTAINED BY SCRIBING FROM A DRAWER WHICH HAS BEEN COMPLETED AND FITTED



SECTION 'D-D'



DETAIL AT 'X'

MATERIAL LIST (Approximate only)

TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	300
2 3/4 ins. x 3/4 in.	40
4 ins. x 3/4 in.	60
4 ins. x 1/2 in.	24
4 3/4 ins. x 3/4 in.	9
6 1/2 ins. x 1/2 in.	20
7 1/4 ins. x 3/4 in.	7
3/16" Masonite Standard Preswood	250 sq. ft.
3/16" Masonite Tempered Preswood	25 sq. ft.
Masonite Pegboard	2 sq. ft.







TABLE PLAN




SECTION 'G-G'




DETAIL AT 'Y'




ALTERNATE LEG DETAIL




PART SECTIONAL VIEW



DETAIL AT 'Z'




LEG DETAIL




FRAME ...
OVERHEAD CABINETS


ELEVATION 2'




SECTION 'A-A'




SECTION 'B-B'




SECTION 'C-C'



ELEVATION '2'
(DOORS & DRAWERS OMITTED)



TYPICAL DRAWER DETAIL



BOTTOM- $\frac{3}{16}$ " MASONITE
STANDARD PRESWOOD
FACE FRONT

FRONT $\frac{3}{4}$ "

1/4" x 5/16" GROOVE
2 SIDES & FRONT

**MASONITE TEMPERED PRESWOOD — FOR EXTERIORS
AND INTERIORS — WHEREVER MOISTURE IS PREVALENT.**



KITCHEN '=' PLAN No. 4

PAGE
17

FRAMES...
OVERHEAD CABINETS




ELEVATION 1

31 ¹/₁₆"

30 ¹/₂"

33 ³/₈"

CLEATS ³/₈ x ³/₄"




SECTION 'E-E'



ALL TIMBER 1 3/4" x 3/4" DRESSED
EXCEPT WHERE OTHERWISE STATED.

FRAME
BASE CABINET
ELEVATION 'I'

NOTE: Material list is intended only as a guide and is not complete for all requirements




MATERIAL LIST (Approximate only)		
TIMBER (Fin. Size)		LIN. FEET
1 3/4 ins. x 3/4 in.		374
2 3/4 ins. x 3/4 in.		25
3 ins. x 3/4 in.		75
4 ins. x 3/4 in.		50
5 ins. 1/2 in.	BASE CABINETS	65
5 3/4 ins. x 3/4 in.		25
3/16" Masonite		
Tempered Presdwood		32 sq. ft.
3/16" Masonite		
Standard Presdwood		240 sq. ft.
1 3/4 ins. x 3/4 in.	TOP CABINETS	280
3/16" Masonite		
Standard Presdwood		160 sq. ft.



SECTION 'D-D'

**MASONITE TEMPRTILE — FOR BATHROOMS, KITCHENS,
FLOORS — WHEREVER "TILING" IS REQUIRED.**













MATERIAL LIST (Approximate only)	
TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	400
2 3/4 ins. x 3/4 in.	4
4 ins. x 3/4 in.	50
5 ins. x 3/4 in.	10
5 ins. x 1/2 in.	30
6 1/2 ins. x 3/4 in.	6
6 1/2 ins. x 1/2 in.	18
3/16" Masonite	
Standard Presdwood	240 sq. ft.
3/16" Masonite	
Tempered Presdwood	20 sq. ft.
1 3/4 ins. x 3/4 in.	200
6 ins. x 3/4 in.	6
3/16" Masonite	
Standard Presdwood	125 sq. ft.
	BASE CABINETS
	TOP CABINETS

NOTE: Material list is intended only as a guide and is not complete for all requirements.

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.

ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.



MASONITE TEMPERED PRESWOOD — THE SUPERIOR FINISH FOR BENCH TOPS, EXTERIOR DOORS AND LININGS.

KITCHEN
'L' PLAN
No. 5

PAGE
19

NOTE: $\frac{3}{16}$ " MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.

FRAME... OVERHEAD CABINETS

FRAME... BASE CABINETS

FRAME... BASE CABINETS










FRAME... BASE CABINETS

BENCH TOPS

LAYOUT OF 4" x 3/4" TIMBER KICK BASE FOR BASE CABINETS SHOWN BELOW

ALL TIMBER 1 1/2" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.


TO SUIT SINK



MASONITE PRIMECOTE — SAVES TIME, ELIMINATES SEALER AND PRIME COATS — WILL TAKE ANY PAINT FINISH.

**KITCHEN
'U' PLAN
No. 6**

**PAGE
21**



FITTING PIVOTED DOORS

1. RECESS AND SCREW PIVOT BRACKETS IN POSITION ON DOOR FRAMES.
2. UNSCREW PIVOT BRACKETS AND PLACE IN RESPECTIVE HOUSINGS (HOLD TOP BRACKET IN PLACE WITH ADHESIVE TAPE).
3. SLIDE DOOR FRAMES BETWEEN BRACKETS.
4. SCREW BOTTOM PIVOT BRACKET ON TO DOOR FRAME WITH DOORS IN ALTERNATE OPEN POSITIONS.
5. REMOVE ADHESIVE TAPE AND FIT TOP BRACKET AS DESCRIBED FOR BOTTOM BRACKET (4).

THIS OPERATION IS SIMPLIFIED BY FITTING BEFORE BENCH TOP AND SIDE SHEETING IS FIXED.


MATERIAL LIST (Approximate only)

TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	375
2 3/4 ins. x 3/4 in.	6
4 ins. x 1/2 in.	10
4 ins. x 3/4 in.	75
6 1/2 ins. x 1/2 in.	18
6 1/2 ins. x 3/4 in.	18
3/16" Masonite Standard Presdwood	240 sq. ft.
3/16" Masonite Tempered Presdwood	32 sq. ft.
1 3/4 ins. x 3/4 in.	232
4 ins. x 3/4 in.	3
3/16" Masonite Standard Presdwood	170 sq. ft.

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.

ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED

NOTE: Material list is intended only as a guide and is not complete for all requirements.




DETAIL FOR HOUSING PIVOT BRACKETS




**MASONITE PRESWOOD — LIFETIME SATISFACTION WITH
MAXIMUM ECONOMY — MADE IN AUSTRALIA FOR
AUSTRALIA.**

**KITCHEN
'U' PLAN
No. 6**

**PAGE
23**




PLAN
GENERAL ARRANGEMENT OF FIXTURES




ELEVATION 'I'

ALL TIMBER 1 3/4" x 3/4" DRESSED
EXCEPT WHERE OTHERWISE STATED.




ELEVATION '2'

BOTTOM 3/16" MASONITE
STANDARD PRESWOOD




TYPICAL DRAWER DETAIL



SECTION 'C-C'

LAMINATE 2 THICKNESSES
OF MASONITE STANDARD
PRESWOOD FOR ALL
SHELVES




SECTION 'D-D'

SECTION 'E-E'

MATERIAL LIST (Approximate only)

TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	220
4 ins. x 3/4 in.	32
5 ins. x 3/4 in.	8
5 ins. x 1/2 in.	15
6 1/2 ins. x 1/2 in.	18
6 1/2 ins. x 3/4 in.	6
3/16" Masonite	
Standard Preswood	130 sq. ft.
3/16" Masonite	
Tempered Preswood	20 sq. ft.
1/4" Masonite	
Tempered Preswood	30 sq. ft.
1 3/4 ins. x 3/4 in.	135
3/16" Masonite	
Standard Preswood	96 sq. ft.
1/4" Masonite	
Tempered Preswood	24 sq. ft.





NOTE: Material list is intended only
as a guide and is not complete for
all requirements.



SECTION 'A-A'

SECTION 'B-B'

CAKE & BREAD BINS
MAY BE LINED WITH
3/16" MASONITE
TEMPERED PRES-
WOOD OR TINPLATE












ALL TIMBER 1 3/4" x 3/4" DRESSED
EXCEPT WHERE OTHERWISE STATED.

NOTE: $\frac{3}{4}$ " MASONITE STANDARD PRESWOOD
USED ON ALL FACES, EXCEPT WHERE OTHERWISE STATED.



KITCHEN '=' PLAN No. 7

PAGE
25




NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.



ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.

MATERIAL LIST (Approximate only)


TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	400
2 1/2 ins. x 3/4 in.	30
5 ins. x 3/4 in.	6
5 ins. x 1/2 in.	18
5 7/8 ins. x 3/4 in.	21
5 7/8 ins. x 1/2 in.	21
4 ins. x 3/4 in.	46
3/16" Masonite Tempered Preswood	22 sq. ft.
3/16" Masonite Standard Preswood	275 sq. ft.
2 1/2" Radius x 16" Width Masonite Structural Bends	3 off—8 ft. long 2 off—6 ft. long
1 3/4 ins. x 3/4 in.	300
2 1/2 ins. x 3/4 in.	25
4 ins. x 3/4 in.	8
5 ins. x 3/4 in.	10
3/16" Masonite Standard Preswood	172 sq. ft.

NOTE: Material list is intended only as a guide and is not complete for all requirements.






LARGE TILE PATTERN (12" x 12") CAN BE CUT WITH MASONITE GROOVER & PAINTED IN CONTRASTING COLOURS ... 3/16" MASONITE STANDARD PRESWOOD SHEETING OR MASONITE PEGBOARD





ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.


BENCH TOP ELEVATION '3'





FRAME... OVERHEAD CABINETS ELEVATION '2'



BENCH TOP ELEVATION '3'




FRAME... BASE CABINET ELEVATION '2'




SECTION 'G-G'

MASONITE STANDARD PRESWOOD — FOR SHELVES, INTERNAL DOORS, CUPBOARDS, INTERIOR LININGS.






FRONT ELEVATION




PLAN


ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.



FRAME...
DRESSING TABLE UNIT



DRESSING TABLE DRAWERS



TRAY TYPE WARDROBE DRAWERS

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.

3/16" MASONITE STANDARD LEATHERBOARD MAY BE USED AS AN ALTERNATIVE SHEETING ON EXPOSED FACES OTHER THAN BENCH TOP

MATERIAL LIST (Approximate only)

TIMBER (Finished Size)	LINEAL FEET
10 3/8 ins. x 3/4 in.	15
9 7/8 ins. x 3/8 in.	27
9 1/8 ins. x 3/8 in.	15
6 7/8 ins. x 1/2 in.	22
5 3/4 ins. x 1/2 in.	15
4 1/4 ins. x 3/4 in.	15
4 ins. x 3/4 in.	60
2 3/4 ins. x 3/4 in.	95
1 3/4 ins. x 3/4 in.	675
3/4 in. x 3/4 in.	150
3/16" Masonite Standard Presdwood	465 sq. ft.
3/16" Masonite Tempered Presdwood	8 sq. ft.

THE POWDER BAR AS SET OUT ON PAGE 32 MAY BE USED AS AN ALTERNATIVE DRESSING TABLE UNIT.


NOTE: Material list is intended only as a guide and is not complete for all requirements.




MASONITE LEATHERBOARD — FOR WALLS AND CEILINGS
... BUILT-IN SEATS, POWDER BARS, WARDROBES ...
SIMULATES SPANISH GRAIN LEATHER.

BUILT-IN
WARDROBE


PAGE
29



SECTION 'A-A'



SECTION 'B-B'




SECTION 'C-C'

3/16" MASONITE STANDARD PRESWOOD WHERE FACES ARE AGAINST A WALL SHEET WITH SCREEN SIDE OUT


ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.



FRAME...
OVERHEAD CUPBOARDS

SIDE UNITS... TWO OFF




FRAME...
OVERHEAD CUPBOARDS


CENTRE UNIT

3/16" MASONITE STANDARD LEATHERBOARD MAY BE USED AS AN ALTERNATIVE SHEETING ON EXPOSED FACES

SEE DETAIL OF LARGE DOOR CONSTRUCTION ON PAGE 12




FRAME... LEFT SIDE UNIT




FRAME... RIGHT SIDE UNIT

WHERE FACES ARE AGAINST A WALL SHEET WITH SCREEN SIDE OUT

NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.




DETAIL AT 'X'
FIXING CUPBOARDS TO CEILING



DETAIL AT 'Y'
PLAN OF DRAWER RUNNER & GUIDE

3/16" MASONITE STANDARD LEATHERBOARD MAY BE USED AS AN ALTERNATIVE SHEETING ON EXPOSED FACES.

ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.



DETAIL AT 'Z'
PLAN OF DRAWER RUNNER & GUIDE


SAME MEASURE AS THICKNESS OF FINISHED DOORS




MASONITE PEGBOARD — ANYTHING FROM PICTURES TO SHELVES, TOOLS TO UTENSILS . . . HUNG EXACTLY WHERE THEY ARE WANTED.

BUILT-IN WARDROBE


PAGE
31




FRONT ELEVATION




SECTION 'A-A'



SECTION 'B-B'




SECTION 'C-C'




HINGED SECTION


NOTE: 3/16" MASONITE STANDARD PRESWOOD USED ON ALL FACES EXCEPT WHERE OTHERWISE STATED.




SECTION 'D-D'




POWDER BAR SEAT



SEAT TOP




SEAT FRAME




FRAME


ALL TIMBER 1 3/4" x 3/4" DRESSED EXCEPT WHERE OTHERWISE STATED.




DETAIL AT 'X'




DRAWER DETAIL




MATERIAL LIST (Approximate only)		
TIMBER (Finished Size)		LINEAL FEET
3/4 in. x 3/4 in.	POWDER BAR	18
1 3/4 in. x 3/4 in.		80
2 1/4 in. x 3/4 in.		5
2 3/4 in. x 3/4 in.		3
4 in. x 3/4 in.		10
3 1/2 in. x 3/4 in.		5
3 1/2 in. x 1/2 in.		9
6 1/4 in. x 3/4 in.		4
6 1/4 in. x 1/2 in.		13
3/16" Masonite Standard Presdwood		48 sq. ft.
3/16" Masonite Tempered Presdwood		8 sq. ft.
1 3/4 in. x 3/4 in.	SEAT	11
2 3/4 in. x 3/4 in.		5
4 in. x 3/4 in.		5
3/16" Masonite Standard Presdwood.		2 sq. ft.
Masonite Pegboard		4 sq. ft.
3/16" Masonite Standard Leatherboard		2 sq. ft.




SECTION 'A-A'




SECTION 'B-B'



SECTION 'C-C'




SECTION 'D-D'



FRONT ELEV'N

END ELEV'N



BACK ELEV'N


ELEVATIONS

(EDGE Mouldings OMITTED)



MATERIAL LIST (Approximate only)

TIMBER (Finished Size)	LINEAL FEET
1 3/4 ins. x 3/4 in.	60
3/4 in. x 3/4 in.	240
4 ins. x 3/4 in.	67
3 1/2 ins. x 3/4 in.	65
3/4 in. Moulding	60
1/8" Masonite Tempered Preswood	130 sq. ft
3/16" Masonite Standard Preswood	125 sq. ft
Masonite Pegboard	96 sq. ft

NOTE: Material list is intended only as a guide and is not complete for all requirements.



ALL TIMBER 1 3/4 x 3/4 DRESSED EXCEPT WHERE OTHERWISE STATED



ASK YOUR MASONITE DISTRIBUTOR OR MERCHANT FOR OUR COMPREHENSIVE RANGE OF FREE TECHNICAL LITERATURE.

ROOM DIVIDER

PAGE 33

and now there are **17** types and thicknesses
of **MASONITE PRESWOOD**
to do a thousand jobs better!


—in the home

—on the farm

—along Commercial Avenue and Industry Road

**Newest member of the
MASONITE PRESWOOD
family!**


**MASONITE
Pegboard**



The first really new panelling idea in years. Ideal for walls and ceilings.


Available in natural brown, matt or glass or Leatherboard two tone finish: all on $\frac{1}{8}$ in. Tempered Presdwood with $\frac{3}{16}$ in. machine punched holes on 1 in. staggered centres. Sheet sizes 4 ft. x 3 ft. and 6 ft. x 4 ft.

**MASONITE
Standard
PRESWOOD**



The original hardboard. Denser than most woods. Hard, smooth surface on one side, screen impression on other. For interior walls, ceilings, etc. In $\frac{1}{8}$ ", $\frac{3}{16}$ ", $\frac{1}{4}$ " and $\frac{5}{16}$ " thicknesses.

**MASONITE
Tempered
PRESWOOD**



World's best known hardboard. Tempered to extra hardness; greater strength, abrasion and weather resistance. In $\frac{1}{8}$ in., $\frac{3}{16}$ in., $\frac{1}{4}$ in. and $\frac{5}{16}$ in. thicknesses.

**MASONITE
Leatherboard**




Offers the luxury and rich appearance of Spanish-grain leather in rigid panel form. Unlimited design possibilities in homes, schools, stores, offices, etc. Standard or Tempered in $\frac{1}{8}$ in. $\frac{3}{16}$ in. thicknesses.

**MASONITE
Temprtile**



Tempered for durability and moisture resistance. Score lines in large panels form attractive 4 in. or 6 in. tile patterns. In $\frac{3}{16}$ in. thickness.

**MASONITE
Primecote**




Standard Presdwood with a sealer primer coat designed to provide a ready prepared base for any type brush or spray treatment. In $\frac{3}{16}$ in. thickness.

**MASONITE
Termite-Treated
Presdwoods**



Standard or Tempered Presdwoods which have been impregnated with a special solution to make them highly resistant to white ants — available in all thicknesses.

**MASONITE
CONCRETE
FORMBOARD**






A special Tempered Presdwood, insuring smooth concrete surfaces, virtually eliminating costly hand finishing. $\frac{1}{4}$ " thickness

guaranteed never to split, splinter or crack...






MASONITE PRESWOOD

SETTING OUT A CABINET FRAME



Add total width of A, B, C, D, E, F together and subtract from overall length (Y). Remainder (M) is length to be equally spaced (in this instance 5 openings).

Note: When adding A, B, C, D, E, F together subtract $1\frac{1}{2}$ " from that total as $\frac{3}{4}$ " is hidden behind each side cabinet. This is to allow fixing and also eliminates the need for a corner timber moulding.



The size and shape of your kitchen, together with proposed or existing stove, refrigerator, sink, etc., will determine the type of kitchen plan most suited for your requirements. The first step is therefore to measure accurately at several heights the dimensions of the kitchen.

The end sections of the side cabinets should be set out in full size, taking all timber measurements from the actual material. This set out will provide the length of all timber members required for the end and partition frames and length of cross members required for the top and bottom frames. In the case of sloping front cabinets, all angle cuts can be taken from this set out.

Where a cabinet is to be fitted between parallel walls, it should be half an inch shorter than the distance between the walls, wood moulding is used to cover the remaining equal spaces. Assuming a kitchen as shown (left), mark the overall size of the three units, i.e. (R), on a set out rod (a set out rod is simply a suitable length of dressed timber, viz., $1\frac{3}{4}$ in. x $\frac{3}{4}$ in.). On the left end of the rod mark the width of the left hand frame section (S), likewise for the right end frame section (T). The length (Y) between the existing markings is the measure of the sink cabinet.


The length (Y) should have added to it the thickness (usually $\frac{3}{4}$ in. nominal) to each end so that the side cabinets will satisfactorily join to it. This means that the two end styles are sometimes made of $2\frac{1}{2}$ in. x $\frac{3}{4}$ in. timber to allow the end styles to show $1\frac{3}{4}$ in.


Working on a door opening as near as possible to 18 in. wide, it will be seen that there is sufficient length to permit five equal door openings. To calculate the actual door width, subtract the two end styles, (each $2\frac{1}{2}$ in. less $\frac{3}{4}$ in., as $\frac{3}{4}$ in. is hidden behind each side cabinet), plus the four intermediate styles (each $1\frac{3}{4}$ in.) from length (Y), divide the remainder by 5: the result is the door width opening. These calculations are then checked by transferring the measurements on to the set out rod. See (4) left.

Finished timber sizes as mentioned in the plans, e.g., $1\frac{3}{4}$ in. x $\frac{3}{4}$ in. are nominal. For correct setting out all sizes should be taken direct from the actual timber used. When ordering from your timber merchant specify finished sizes — dressed all round. A light sanding of all timber to be used before assembly will make for neater jobs. Base cabinet doors are approximately 18 in. wide and overhead doors 16 in. wide.

PAINING AND FINISHING

We publish a free technical leaflet on painting and finishing of Masonite Presdwoods — many leading paint manufacturers also issue technical literature on painting Masonite Presdwoods. However, in almost every type of furniture paint treatment it is essential to use either a pigmented or clear sealer prior to under or finishing coats on Masonite Presdwoods. A cut back with 320 wet or dry paper between coats will enhance the finished appearance.







KITCHEN 'U' PLAN No. 8 (Pages 26-28)

Easily constructed with Masonite Presdwoods and easy to use Masonite Structural Bends, this kitchen plan incorporates modern features with integrated pelmet box, recessed sink cabinets and virtually dust free cabinets. The tea towel rack will prove a most handy asset. Masonite Pegboard adds efficiency as a utensil rack, and the convenient layout of the kitchen will be most appreciated in the small home.


BUILT-IN WARDROBE (Pages 29-31)

It is easy to adapt this wardrobe to suit your room dimensions by following the principles of cabinet construction as shown on page 36. Simple construction and sturdy Masonite Presdwood together with Masonite Pegboard and Leatherboard create an air of distinction, charm and functional utility. If desired, the Powder Bar (page 32) may be used as an alternative dressing table.



POWDER BAR (Page 32)

The lady of the house will be delighted by this attractive powder bar with its modern design and simple clean lines. Fitted as an alternative to the built-in wardrobe, this powder bar is a smart accessory to either bathroom or bedroom.





ROOM DIVIDER (Page 33)

Designed for the future T.V. set, this handsome room divider has provision for radiogram or tape recorder, built-in speaker, record storage, books, glassware and adjustable shelves for table linen.

COMBINATION BED (Page 35)

Parents will appreciate the straight clean lines, the storage space for toys, shoes, clothing, and all those odds and ends so dear to the heart of a child. Illustrations show bed complete and:

- (1) without foot unit,
- (2) without foot or head unit,
- (3) without head unit.



1




2



3

MASONITE SHORTS*


We are now able to offer a wide range of Masonite 'Shorts'. Many varieties, sizes and thicknesses are now available and will prove to be most economical for the handy man who may not require the large 12 feet by 4 feet sheet. Masonite 'Shorts' are particularly useful for shelves, cupboards, drawer bottoms, etc. It is a wise precaution to always pre-expand Masonite 'Shorts'. You'll find full instructions on page 12.




***SHORTS...** *Useful Masonite Presdwood*

ALUMINIUM AND PLASTIC MOULDINGS


EXTERNAL CORNER
(RIBBED)
*MA.21




DIVISION
(RIBBED)
*MA.22




INTERNAL CORNER
(RIBBED)
*MA.23



SINGLE EDGE
(RIBBED)
*MA.24




DOUBLE EDGE
(RIBBED)
MA.25




*Available in both Plastic and Aluminium. All mouldings are in 12 feet lengths and suitable for both 3/16 in. and 1/8 in. Masonite Presdwood.


EXTERNAL CORNER
(PLAIN)
MA.26



DIVISION
(PLAIN)
MA.27




INTERNAL CORNER
(PLAIN)
MA.28




SINGLE EDGE
(PLAIN)
MA.29



WAIST
(PLAIN)
MA.32



SKIRTING
(PLAIN)
MA.31



MASONITE TOOLS


PAINT STRIPER

For lining grooves in Temprtile or grooved designs.



PRE-PUNCH

For easier nailing of Masonite Presdwood.



GROOVER

For grooved designs on Masonite Presdwood.



Here's how Masonite Presdwood* can . . . help you in your home!



*** Masonite Presdwood is the
world's finest building board**

Whether it's a new home or a remodelling job, wonderful versatile Presdwoods will prove to be a lifelong investment. Masonite Presdwoods are the only hardboards which, properly applied, won't chip, warp or crack. Masonite Tempered Presdwood is ideal for all hard wearing surfaces and as an exterior wall covering (either flat wall or as a weatherboard). Many Architects specify Tempered Presdwood for flat roof decking — millions of home-owners all over the world use Masonite Standard Presdwood for interior linings — for walls, ceilings, cupboards, shelves and all the hundred and one places that go to make the perfect home — you'll enjoy using Masonite Presdwoods — the world's finest building boards.

MASONITE BRAND PRODUCTS


- Masonite Standard Presdwood
- Masonite Tempered Presdwood
- Masonite Temprtile
- Masonite Primecote
- Masonite Leatherboard
- Masonite Concrete Formboard
- Masonite Pegboard *
- Masonite Termite-Treated Presdwood

All in big 12 feet by 4 feet sheets

* Masonite Pegboard: 6 feet by 4 feet




Both in new and old homes, versatile Masonite Leatherboard is ideal for wall panelling. It does the job so rapidly, inexpensively, yet is luxurious.




Low in cost, high in appeal, ceilings of Masonite Presdwood can be simply or intricately grooved for added charm.



Old floors take on new beauty when they are covered with super-tough, easily applied Masonite Tempered Presdwood.



Smooth, large, easy-to-handle sheets of Masonite Presdwood make the perfect material for durable and convenient built-in furniture.



Masonite Temprtile makes the ideal wall surface for kitchens, bathrooms and laundries. Masonite Presdwood for the built-in cupboards, of course.

MASONITE CORPORATION (AUSTRALIA) LIMITED

Works and Forests: Raymond Terrace, N.S.W.

PRINCIPAL SALES OFFICE: 533 COLLINS ST., MELBOURNE

STATE SALES OFFICES:

31 CHESSER STREET, ADELAIDE

282 QUEEN STREET, BRISBANE

369 PITT STREET, SYDNEY

A. E. KEATING PTY. LTD.
535 50M 1/55 E.J.